



RTX-A10

DFB 博思电子
ELECTRONIC

STURDY OUTDOOR RENTAL SMD SCREEN



Our design for RTX series panel is based on the ideas and wishes of spectacular stage show application. it is not only extremely sturdy, yet still compact and light weight, but also absolutely reliable...

The quick lock system, plus the neutrik power and signal connector gives super convenience for the fast setup, two person can finish 12sqm led panels installation in 30min without any special or complex tools, it benefits you in every business...

in considering of the completely outdoor working environment, we applied the new outdoor SMD technology for the RTX LED Panels, it makes the high resolution, high brightness, Anti-UV protection, pure color contrast come true for the outdoor led display application.

More you'll enjoy...we are expecting...

- Tel.: +86 (28)65018121
- E-Mail: sales@dongfangled.com
- Internet: www.dongfangled.com
- <http://dongfangled.en.alibaba.com>



RTX-A10

LEDs Sources

LEDs	16,384 SMD3535 LEDs
Colors	16.384xred, 16.384xgreen, 16.384x blue
Diffuser	No
LED-Pixel Pitch	10 mm
LEDs density/sqm	10,000
Brightness	6,000 nits
Color mixing	1R1PG1B
LED life	> 80000 hours
Pixel error rate	3/10.000
LED wavelengths	Red: 615-620nm, Green: 515-520nm, Blue: 465-470nm

Specifications

Voltage	100-260 V 50-60 Hz
Power consumption max.	400Watts
Power consumption Ave.	200Watts

Optical System

Optics	Fixed optical systems
Angle	110° horizontal / vertical

Tiles

Material	Aluminum
Color	black
Tile protection class	IP65/IP54

Dimensions / weight

Dimensions (L x W x H)	640 x 640 x 87 mm
Weight	15 Kg
Mounting	Fast Lock System
Certificates	CE, RoHs

Temperature Ranges

Ambient temperature	-30°/+60° C
Operating	Max. 60° C
Cooling	PSU fan

Control and Programming

Protocol	DVI
Control software	Dbstar LED/Linsn Studio
Control terminal	Neutrik push-pull
Refresh rate	400 Hz~2000Hz available
Gray level	12 Bits~16Bits available

Special Features

- Compact & easy operation design
- Integrated complete electronics in the panel
- No additional ethernet-switch/PSU necessary
- Short-circuit protection
- Neutrik push-pull data & power connector
- Intuitive configuration via graphical user interface /no setting of address required
- Control via DVI/HDMI interface
- Compatible with standard media servers

- Tel.: +86 (28)65018121
- E-Mail: sales@dongfangled.com
- Internet: www.dongfangled.com
- http://dongfangled.en.alibaba.com

