

INDUSTRIAL LIGHTING SOLUTIONS



LED LOW BAY & HIGH BAY LAMP

GENERAL FEATURES:

- Sturdy high shock & vibration resistant construction with one high power LED light source, patented aluminum heat sink and highly-reflective optical diffuser cone.
- Available from 30W-150W in color temperature from 3000K through 7500K.
- No UV radiation emitted; no Mercury; no Infrared Radiation; no ballast required.
- 30,000 hours longer life time than incandescent & fluorescent with over 50% savings in energy consumption.
- Solid-state wide voltage and constant current design with no noise or flickering.
- Operate in accordance with UL, ETL, CE and FCC testing standards, Instant on and instant off.

DF-I-01 SERIES



UNIQUE FEATUERS:

30W-100W

- Integrated High Power & High Efficiency LED Chips
- Superb Price/Performance Ratio
- Most Economical Solution to Replace HPS&HID
- Wide Input Voltage from AC120V to AC277V
- Recommended Mounting Height: < 6 Meters

DF-I-02 SERIES



UNIQUE FEATURES:

70W-150W

- Patented Micro-Groove Composite Phase Change Cooler with Superb Cooling Heat Conduction Effect of $400\text{W}/\text{cm}^2$ Which Is 1000 Times of Water-Cooling System and 100 Times of Heat Pipe Cooling System
- Low Working Temperature($<50^{\circ}\text{C}$) of LED chips
- Much More Stable Than Water-Cooling and Heat Pipe Cooling System
- UL Listed Driver with Wide Input Voltage from AC120V to AC277V
- Recommended Mounting Height: 150W LED High Bay at 8 Meters

DF-M-01 SERIES**UNIQUE FEATURES:****50W-100W**

- Multiple-Chip Solution Provides Much More Uniform Glow and Good Heat Conduction
- UL Listed Driver with Wide Input Voltage from AC120V to AC277V
- High efficiency LED Light Sources
- Recommended Mounting Height < 6 Meters

LED HIGH BAYS ON DEVELOPING**DF-M-02 SERIES****150W-200W**

Coming Soon...